

SaveCombinationCodes (POST)

Overview

This POST API can be used to capture new additions in bulk Combination Code details from ERP into SMART by GEP, that can be used as reference in P2P transactions.

URL Format: <https://<Instance>/SmartBulkInterfaceAPI/api/CombinationCodes/SaveCombinationCodes>

Request

```
[
  {
    "Code": "String",
    "Status": 'Char',
    "lstOrgEntity": [
      {
        "EntityCode": "String",
        "IsDefault": true,
        "EntityType": "String",
        "LOBEntityCode": null
      }
    ]
  }
]
```

Response

```
{
  "statusCode": 202,
  "url": "String",
  "batchID": "String",
}
```

```

    "interval": 00,
    "interval Type": "String",
    "receivedCount": 0
}

```

Data Elements

CombinationCode				
Property	Required?	Data type	Description	Validations/Exceptions
Code	Yes	String	Code of entity	<ul style="list-style-type: none"> Code is mandatory Validation failed for code combination Number of codes are not matching with entities configured
Status	No	Char	Status of the entity	
LstOrgEntity	No	List of OrgEntity object	Check data type OrgEntity for details	

LstOrgEntity				
Property	Required?	Data type	Description	Validations/Exceptions
EntityCode	No	String	Entity Code of the entity	<ul style="list-style-type: none"> Invalid EntityCode
IsDefault	No	Boolean	A flag used to denote if entity is the default or not	
EntityType	No	String	Entity Type of the entity	<ul style="list-style-type: none"> Invalid EntityType
LOBEntityCode	No	String	Line of Business Entity Code of the entity	<ul style="list-style-type: none"> Invalid LOBEntityCode

Examples

Success Scenario – Request

Request below describes that this contains only the mandatory attributes:

```

[
{

```

```
"Code": "10|0420|20|6150000|00000",
"Status": "A",
"lstOrgEntity": [
  {
    "EntityCode": "CBAD",
    "IsDefault": true,
    "EntityType": "BusinessUnit",
    "LOBEntityCode": null
  }
]
]
```

Success Scenario – Response

```
{
  "statusCode": 202,
  "url": "https://<instance>/SmartBulkInterfaceAPI/api/BulkResult/GetBulkResult?batchId=110e7c8551f647c39726b8e9e7ec2980",
  "batchID": "110e7c8551f647c39726b8e9e7ec2980",
  "interval": 60,
  "interval Type": "Seconds",
  "receivedCount": 10
}
```

Error Scenario – Request

Request has a missing value of the Authorization Header which is mandatory: (401 – Unauthorized)

Error Scenario - Response

Access to interface BulkAPI is denied, Authorization Header is missing.